

FLETCH RODDING EYES

Fletcher **RODDING EYES**

Point Drainage System

Fletcher Rodding Eyes



Fletcher RODDING EYES are elements drains are used in industrial facilities. Rodding Eyes enable fast, efficient and extremely easy access to the sewage system and underfloor gives you the opportunity to maintain a pure product through easy cleaning of the body. Revisions are made of AISI304 or AISI316 stainless steel.

Fletcher RODDING EYES :

- > Rodding eyes with covers
- > Types of covers
- > Revisions to the filling

27

28

29

Fletcher RODDING EYES

FLETCH RODDING EYES

DRAINAGE POINT SYSTEM

Rodding Eyes with covers



Excellent corrosion resistance



Stop-odor effect



Dimension offered revision is flexible and adapted to the diameter of the sewer


Fletch RODDING EYES are elements drains are used in industrial facilities. Rodding Eyes enable fast, efficient and extremely easy access to the sewage system and underfloor gives you the opportunity to maintain a pure product through easy cleaning of the body. Revisions are made of **AISI304 or AISI316 stainless steel**.

There are two types of rodding eyes covers: smooth and grooved. Finish the edge enables development in any type of floor covering.

EXAMPLE OF MARKING THE CATALOG:

Fletch RODDING EYES

FRP - 150 - D110



Part of the continuing tightness and which prevents leakage of water and waste is small GASKET, mounted between the bolt-cover and the housing.

Finish the edges allows development in any type of floor.

Fletch rodding EYES 6 STANDARD SIZES:

Symbol	W	H	DN
FRP-150-D110	150x150	150	110
FRP-200-D110	200x200	150	110
FRP-200-D160	200x200	150	160
FRP-250-D160	250x250	150	160
FRP-250-D200	250x250	150	200
FRP-300-D200	300x300	150	200

ACCESSORIES:

- screw
- Plate (smooth or grooved)



Fletcher
RODDING
EYES

FLETCHER RODDING EYES

DRAINAGE POINT SYSTEM

Types of
covers



RODDING EYES WITH SMOOTH COVERS

- usually used in load class **L15-M125** (foot traffic - heavy traffic)



RODDING EYES WITH GROOVED COVERS

- anti-slip
- commonly used in the class load **L15** (foot traffic)

SELECTION OF THE APPROPRIATE COVER

CLASS LOAD [L15 - M125]



Technical conditions, the strength of the product load weights affect the selection of the cover. Eg. Cover grooved may be used only with pedestrian traffic [class L15], and smooth with an appropriate strengthening of the structure, even in the classroom M125 (heavy traffic).

ANTI-SLIP PROPERTY



The standards and requirements for safety and construction pay attention to maintaining adequate security in each product, which is a component of the investment. Therefore, the cover has a grooved anti-slip feature, allowing you to avoid accidents in rooms with wet floor.



Fletcher RODDING EYES

FLETCH RODDING EYES

DRAINAGE POINT SYSTEM

Revisions to the filling



The perfect product for those who prefer a nice, uniform design floors, thanks to the ability to adapt to fill their needs.



Stop-odor effect




Dimension offered revision is flexible and adapted to the diameter of the sewer

Fletch RODDING EYES are elements drains are used in industrial facilities. Rodding Eyes enable fast, efficient and extremely easy access to the sewage system and underfloor gives you the opportunity to maintain a pure product through easy cleaning of the body. Revisions are made of **AISI304** or **AISI316** stainless steel.

EXAMPLE OF MARKING THE CATALOG:

Fletch RODDING EYES FRPW - 200 - D110



Part of the continuing tightness and which prevents leakage of water and waste is small **GASKET**, mounted between the bolt-cover and the housing.

Finish the edges allows development in any type of floor.

Fletch rodding EYES 5 STANDARD SIZES:

Symbol	W	H	DN
FRPW-200-D110	200x200	150	110
FRPW-200-D160	200x200	150	110
FRPW-250-D160	250x250	150	160
FRPW-250-D200	250x250	150	160
FRPW-300-D200	300x300	150	200

ACCESSORIES:

- screw